

		MODEL 9220	MODEL 9430	5200 DRAPER / 9125 AUGER
<b>ENGINE</b>				
Model		Cummins (Turbocharged) B3.3T	SisuDiesel (Turbocharged & Intercooled) 4.4 CTA	
HP		85	120	18, 22, 25, 30, 36 (5.5, 6.7, 7.6, 9.1) 22, 25, 30 (6.7, 7.6, 9.1)
Drive System Type		Hydrostatic with planetary final reduction	Hydrostatic with planetary final reduction	Hydraulic
Speed Range: mph (kph)		0-11 (0-17.7)	0-15 (0-24)	Over-serrated sections and forged guards
Transmission		Single Speed	Dual Speed	Hydraulic motor and SCH gearbox, 1300 strokes/min.
<b>CAPACITIES</b>				Hydrostatic motors, speed control from cab, 0-60 rpm
Fuel Tank: gal. (l)		80 (227)	80 (227)	41 in (1,040 mm) rubberized
<b>TIRES</b>				Hydrostatic motors, speed control from cab, 0-600 ft/min.
Front: turf		18.4 x 26 turf tread	18.4 x 26 turf tread	54-70 (1,370-1,780)
Front: bar tread		16.9 x 28 R4 bar tread & 18.4 x 26 RI bar tread	16.9 x 28 R4 bar tread & 18.4 x 26 RI bar tread	
Rear caster: implement rib - Adj, Axle - Fixed Axle		14.1 x 16.1 12.5L - 15	14.1 x 16.1 12.5L - 15	
<b>DIMENSIONS</b>				
Length with header in. (mm)		257.6 (6,543)	257.6 (6,543)	14, 16 or 18 (4.3, 4.9 or 5.5)
Wheelbase: in. (mm)		140 (3,556)	140 (3,556)	5-bat with camtrak steel flex tines
Width with 18.4 tires: in. (mm)		146.5 (3,722)	146.5 (3,722)	Dual sickles, 1,840 strokes/min., hydraulic swaybar drive
Front tread width: in. (mm)		127.6 (3,241)	127.6 (3,241)	3 (76)
Rear tread width: in. (mm) - Adj, Axle - Fixed Axle		84.4 - 120 (2,144 - 3,048) 120 (3,048)	84.4 - 120 (2,144 - 3,048) 120 (3,048)	9 (229)
Underframe clearance: in. (mm)		39.8 (1,010)	39.8 (1,010)	10 (254)
Height to top of cab: in. (mm)		130.9 (3,324)	130.9 (3,324)	110 (2,794)
Weight without header: lbs. (kgs)		8,100 (3,674)	8,300 (3,765)	Engaging Steel-Steel or Rubber-Steel
<b>CAB</b>				<b>OPTIONAL TRACTOR EQUIPMENT</b>
Comfort		Quiet cab, A/C and heater, air ride seat and tilt steering wheel, tinted glass	Quiet cab, A/C and heater, air ride seat and tilt steering wheel, tinted glass	Windshield wiper kit
<b>CONTROLS</b>		Ground speed, throttle, header engagement, parking brake, full instrumentation	Ground speed, throttle, header engagement, parking brake, full instrumentation	AMI/FM Radio and CD, with weatherband
<b>LIGHTS</b>		5 front halogen, 2 rear cab halogen, 2 rear tractor halogen, 4 amber flashers	5 front halogen, 2 rear cab halogen, 2 rear tractor halogen, 4 amber flashers	Tractor performance monitor
				Rotary screen (Model 9220)
				Easy attach header angle kit
				Quick couplers
				Hydraulic guard angle (Model 9220)
				Header Height Indicator