

# There is only 1 choice when it comes to protecting your investment



# **Online Lubricant Guide**

Access our Online Lubrication Guide and discover the correct lubricants for your machine. Includes data on many brands and models, and safety data information.

**Click here** to access the Online Lubrication Guide.

- 4 Engine Oils
- 7 Multi-Functional Oils
- 10 Transmission Oils
- 11 Hydraulic Oils
- 12 Gear Oils
- 13 Goolant
- 14 Grease
- 14 Clutch & Brake Fluids



MASSEY-FERGUSON (Also see AGCO) [Tractors] MF-4800, MF-4840, MF-4880, MF-4900

Crankcase - Cummins V/VT-903 Engs Service Refill Capacity: 32\* Litres.

# **Engine Oils**



## **AGCO ULTRA PLUS**



AGCO ULTRA PLUS is the very latest specification engine designed to meet the latest emission requirements. For use in engines with Diesel Particulate Systems (DPF), Diesel Oxidation Catalyst (DOC), Exhaust Gas Recirculation (EGR) and SCR catalyst or any combination of above technologies. Designed for Tier 4 and above engines and is also backward compatible.

# Specifications

ACEA E9/E7 API CK-4/CJ-4 SAE 15W-40

## **Meets The Following**

CAT ECF-3
CUMMINS CES 20086
DEUTZ DQC III-10 LA
DETROIT DIESEL DDC 93K222
MACK EO-S 4.5
VOLVO VDS-4
MAN M 3775
MTU DDC TYPE 2.1
VOLVO VDS 4.5

#### **Part Numbers**

5L AP1210005 20L AP1210020 205L AP1210205 1000L AP1211000

# **AGCO PREMIUM PLUS**



A super high performance diesel engine oil formulated to cope with a variety of conditions and the harshest environments. For all AGCO Machines Tier 3 and earlier. AGCO Premium Plus provides great protection from corrosion and high continuous stress. AGCO Premium Plus can be used in tractors, trucks, passenger cars and industrial equipment.

# Specifications

ACEA E7 API CI-4/SL GLOBAL DHD-1 SAE 15W-40

# Meets The Following

CUMMINS CES 20076, 77, 78
DETROIT DIESEL 93K215
DEUTZ DQC III-10
MACK EO-N
MAN M 3275-1
MB 228.3
MTU DDC TYPE 2
VOLVO VDS-3
RENAULT RLD/RLD-2

# Part Numbers

5L AP1110005 20L AP1110020 205L AP1110205

# **Engine Oils**



# **MASSEY FERGUSON ULTRA PLUS**



MASSEY FERGUSON ULTRA PLUS is the very latest specification engine designed to meet the latest emission requirements. For use in engines with Diesel Particulate Systems (DPF), Diesel Oxidation Catalyst (DOC), Exhaust Gas Recirculation (EGR) and SCR catalyst or any combination of above technologies. Designed for Tier 4 and above engines and is also backward compatible.

# **Specifications**

ACEA E9/E7 API CK-4/CJ-4 SAE 15W-40

## **Meets The Following**

CAT ECF-3
CUMMINS CES 20086
DEUTZ DQC III-10 LA
DETROIT DIESEL DDC 93K222
MACK EO-S 4.5
VOLVO VDS-4
MAN M 3775
MTU DDC TYPE 2.1

#### **Part Numbers**

20L MF1210020 205L MF1210205



# **AGCO OPTIMUM PLUS**



AGCO OPTIMUM PLUS is a fully synthetic high performance diesel engine oil. The sophisticated additive technology and fully synthetic base oil technology make this a best in class diesel engine oil for a wide range of applications. Provides increased fuel economy for highly loaded commercial diesel engines. For use in Fendt tractors requiring Deutz DQC IV-10-LA approved oils. Can also be used in other applications including other tractor brands, trucks and industrial equipment.

# Specifications

ACEA E9/E7/E6 API CJ-4 SAE 10W-40 JASO DH-2

# **Meets The Following**

VOLVO VDS 4.5

DEUTZ DQC IV-10-LA MAN 3271-1, MAN M 3477 MTU Type DDC 3.1 CAT ECF-3 MB 228.5 MACK EO-OPP VOLVO VDS-4

**CUMMINS CES 20081** 

# **Part Numbers**

20L AP1310020 205L AP1310205

# **Engine Oils**



# **TITAN CARGO MC 10W-40**



TITAN CARGO MC SAE 10W-40 is a super long life, fuel economy engine oil for all diesel engines with and without turbocharger in trucks, buses and industrial machinery. The SAE Class 10W-40 ensures reliable all-season use. Suitable for the longest oil change intervals.

For use in Fendt 1000 S4 Series, as well as other applications.

# Specifications

ACEA E7/E4 API CI-4 GLOBAL DHD-1

#### **Approvals**

MAN M 3277
CUMMINS CES 20077
CUMMINS CES 20078
DEUTZ DQC III-10
DETROIT DIESEL 93K215
MB APPROVAL 228.5
MACK EO-M PLUS
MACK EO-N
MTU DDC TYPE 3
RENAULT RXD
RENAULT RLD-2
SCANIA LDF-2

#### **Part Numbers**

20L FU3359020



## **TITAN CARGO MAXX SAE 5W-30**



TITAN CARGO MAXX SAE 5W-30 is a premium low SAPS engine oil with the innovative XTL®-Technology developed for commercial vehicles. The XTL®-Technology (Xtreme Temperature Lubrication) offers maximum fuel economy over the whole drain-interval due to outstanding oxidation and ageing stability.

For use in Fendt 900 Gen 6 & 1000 G2 Series and Massey Ferguson Ideal Combines, as well as other applications.

# **Specifications**

ACEA E9/E7/E6/E4 API CJ-4 CAT ECF-3 JASO DH-2 SCANIA I A

#### **Approvals**

VOLVO VDS-3

MAN M 3271-1 MAN M 3477 MAN M 3575 MAN M 3677 DEUTZ DQC IV-10 LA DETROIT DIESEL 93K218 MACK EO-O PREMIUM PLUS MTU DDC TYPE 2.1 & 3.1 MB APPROVAL 228.31 MB APPROVAL 228.51 VOLVO VDS-4 SCANIA LDF-4

#### **Part Numbers**

20L FU4726020





# **Multifunction Oils**



#### AGCO V-TRANS



AGCO V-TRANS PLUS 10W-40 is a super high performance multi-functional low friction transmission/hydraulic oil. Designed and selected by AGCO as the premium choice for your tractor fleet, its superior formulation ensures optimum performance, reliability and longevity of your transmission and hydraulic components. Other applications include manual transmissions, hydraulic aggregates and final drives with or without wet brakes and multiplate differentials. Suitable for use as an engine oil in Tier 2 diesel engines pre 1998. A fully approved oil for use in Massey Ferguson tractors transmission and hydraulic reservoirs where Dyna-6. Dyna-4. Dyna VT and earlier transmissions Also for use in Fendt Vario transmissions

# Specifications

SAE J300: 10W-40 API GL-4 API CG-4

#### **Approval**

MF CMS M1145

# **Meets The Following**

FENDT KDM 41.2011
ZF TE-ML 06B, 06F, 07B
SAE J306: 75W-90
DIN 51524-3:HVLP
CASE MS 1207,1209,1210,1230
CNH MAT 3505,3509,3525,3526
NEW HOLLAND 82009201/1/2/3
ZF TE-ML 06A,06C, 06L
JOHN DEFRE JDM J20C

#### **Part Numbers**

5L AP2110005 20L AP2110020 205L AP2110205 1000L AP2111000

## AGCO SPECIAL TRANSMISSION OIL



AGCO SPECIAL TRANSMISSION OIL is a Universal Tractor Transmission Oil for use in Valtra and Challenger equipment. For use in transmissions, hydraulics with integrated wet brakes, clutches and construction machinery. Meets the requirement of a number of tractor brands.

## Specifications

SAE J300: 10W-30 API GL-4

## Meets The Following

VALTRA G2-08, G2-B10
MF CMS M 1143, 1141, 1135
KUBOTA UDT FLUID
ZF TE-ML 03E, 06K, 05F,17E, 21F
(ZF002183)
AGCO Powerfluid 821 XL
AGCO Q 186 (Whitefarm)
ALLISON C-4
CASE 1230,10,09,07,06
CLASS/LADINI - same trans
CNH MAT 3505, 3506, 3509, 3525, 3526, 3540
JOHN DEERE JDM JC20C
NEW HOLLAND 410 B

## **Part Numbers**

5L AP2210005 20L AP2210020 205L AP2210205

# **Multifunction Oils**

# 7

#### AGCO CENTURY MULTI USE TRANSMISSION OIL



AGCO CENTURY 20W-40 is specially formulated for use in pre 2002 farm machinery. Suitable for use in engine, tranmissions, hydraulics, wet brakes and axles.

Designed for older equipment pre 2002.

Specifications

SAE 20W-40 API CE API GL-4 STOU Meets The Following

MASSEY FERGUSON M1144, M1139, M1135 JOHN DEERE: J27 CASE MS1120, MS 1118, MS 1103

FORD/NH M2D-159A-B3/C3, M2 86A

**Part Numbers** 

20L AP2310020

## **MASSEY FERGUSON V-TRANS PLUS**



MASSEY FERGUSON V-TRANS PLUS 10W-40 is a super high performance multi-functional low friction transmission/hydraulic oil. Designed and selected by AGCO as the premium choice for your tractor fleet, its superior formulation ensures optimum performance, reliability and longevity of your transmission and hydraulic components.

Other applications include manual transmissions, hydraulic aggregates and final drives with or without wet brakes and multiplate differentials. Suitable for use as an engine oil in Tier 2 diesel engines pre 1998.

A fully approved oil for use in Massey Ferguson Tractors transmissions and hydraulic reservoirs

where Dyna-6, Dyna-4, Dyna VT and earlier

transmissions.

Specifications

SAE J300:10W-40 API GL-4 API CG-4 **Approval** 

MF CMS M1145

**Meets The Following** 

FENDT KDM 41.2011
ZF TE-ML 06B, 06F, 07B
SAE J306: 75W-90
DIN 51524-3:HVLP
CASE MS 1207,1209,1210,1230
CNH MAT 3505,3509,3525,3526
NEW HOLLAND 82009201/1/2/3
ZF TE-ML 06A,06C, 06L
JOHN DEFRE JDM J20C

Part Numbers

20L MF2110020 205L MF2110205



# **Multifunction Oils**



#### **FENDT V-TRANS PLUS**



FENDT V-TRANS PLUS 10W-40 is a super high performance multi-functional low friction transmission/hydraulic oil. Designed and selected by AGCO as the premium choice for your tractor fleet, its superior formulation ensures optimum performance, reliability and longevity of your transmission and hydraulic components.

Other applications include manual transmissions, hydraulic aggregates and final drives with or without wet brakes and multiplate differentials. Suitable for use as an engine oil in Tier 2 diesel engines pre 1998. AGCO Australia approved for use in Fendt tractors and transmissions and also Fendt transmissions and hydraulics requiring FENDT KDM 41.2011 approved fluids.

## Specifications

SAE J300:10W-40 API GL-4 API CG-4

## Approval

MF CMS M1145

# Meets The Following

FENDT KDM 41.2011
ZF TE-ML 06B, 06F, 07B
SAE J306: 75W-90
DIN 51524-3:HVLP
CASE MS 1207,1209,1210,1230
CNH MAT 3505,3509,3525,3526
NEW HOLLAND 82009201/1/2/3
ZF TE-ML 06A,06C, 06L
JOHN DEERE JDM J20C

## **Part Numbers**

20L FD2110020 205L FD2110205



# **Transmission Oils**



# **AGCO OPTIMUM TRANSMISSION 50**

downtime.



For use in Challenger tractor reaction arm applications as well as heavy duty transmissions. AGCO OPTIMUM TRANSMISSION 50 is a synthetic lubricant that is formulated for extended drain intervals. It is highly stable when exposed to heat, oxidation and shear condtions. Provides

For use in Challenger tractor reaction arms.

exceptional high temperature lubrication as well as providing reduced maintenance and

# **Specifications**

EATON PS-164 rev 7

API MT-1

Meets The Following

#### **Part Numbers**

5L AP8210005



# **ATF PREMIUM ATF D3**



Semi-synthetic automatic transmission fluid. Excellent thermal stability and superior viscometrics improves transmission life. For use in AGCO machinery applications.

# Specifications

DEXRON ® III FORD MERCON ®

# **Meets The Following**

ALLISON C-4 CAT TO-2

#### **Part Numbers**

5I AP8110005

# **Hydraulic Oils**



#### **AGCO HYDRAULIC 68 HVI**



AGCO HYDRAULIC 68 HVI is a high quality ISO 68 hydraulic oil for use in tractors, construction and industrial machinery. It is formulated to resist ageing and oxidation as well as staying in grade to hold viscosity as well as reducing seal leakage. In high pressure hydraulic systems it is critical that the viscosity characteristics of the oil are not diminished with shear losses. AGCO HYDRAULIC 68 HVI contains VI Improvers to ensure product stays in grade.

# Specifications

ISO 68
AFNOR E48-603
FORD MC-6C32
US STEEL 126,127
DENISON HFO
BOSCH REXROTH
VICKERS

## Meets The Following

CINCINNATI MILACRON P-68, P-69, P-70

## **Part Numbers**

20L AP4210020 205L AP4210205

# **AGCO HYDRAULIC 46 HVI**



AGCO HYDRAULIC 46 HVI is a high quality ISO 46 hydraulic oil for use in tractors, construction and industrial machinery. It is formulated to resist ageing and oxidation as well as staying in grade to hold viscosity as well as reducing seal leakage. In high pressure hydraulic systems it is critical that the viscosity characteristics of the oil are not diminished with shear losses. AGCO HYDRAULIC 46 HVI contains VI Improvers to ensure product stays in grade.

# Specifications

ISO 46
AFNOR E48-603
FORD MC-6C32
US STEEL 126,127
DENISON HFO
BOSCH REXROTH
VICKERS

#### Meets The Following

CINCINNATI MILACRON P-68, P-69, P-70

## Part Numbers

20L AP4110020 205L AP4110205

# AGCO SUPERIOR HYDRAULIC OIL



A synthetic oil designed for use in combines and equipment requiring a product that stays in grade and can stand up to the most arduous farming conditions. The shear stable high viscosity index (HVI) and unique additive pack offers a thicker lubricating film at high temperatures and a better high pressure stability which reduces wear and leakages within the system. The combination of group synthetic base oils with carefully selected additives guarantees the improvement of lower temperature properties compared to HVI conventional hydraulic oils.

An ideal in-harvest solution.

# **Specifications**

ISO 46 DIN 51-524: 3 HVLP ISO 6743-4:HV

# Meets The Following

DENSION HFO-T6H20C: HYBRID PUMP BOSCH REXROTH TEREX VICKERS 35VQ-25/ V104-C:VANE PUMPS US STEEL 127,136 CINCINATTI MILA-CRON P68, P69, P70

# Part Numbers

20L AP4310020

# **Gear Oils**



# **AGCO SUPER GEAR 85W-140**



AGCO SUPER GEAR 85W-140 is a super high performance gear oil for extended drain intervals. Formulated to meet the requirements of AGCO machinery and designed to cope under pressure in the heat of the season. Also suitable for a large range of brands including agricultural and construction machinery, as well as light and heavy commercial vehicles.

# **Specifications**

SAE 85W-140 API GL-4/GL-5

# **Meets The Following**

ZF TE-ML 05A ZF TE-ML 12E ZF TE-ML 16D ZF TE-ML 21 A MIL -L-2105 D

#### **Part Numbers**

5L AP3210005 20L AP3210020

# **AGCO SUPER GEAR LS 80W-90**



AGCO SUPER GEAR LS 80W-90 is a super high performance gear oil for all highly stressed normal and limited slip differentials in tractors, cars, trucks, construction and industrial machinery. Can be used where SAE 80W-90 GL-5 is specified.

# **Specifications**

SAE 80W-90 GL-5/GL-5 LS API MT-1 SAE J 2360

# **Meets The Following**

MACK GO-J MIL-PRF-2105 EZ ZF TE ML-07/ML-08

# **Part Numbers**

5L AP3110005 20L AP3110020 205L AP3110205

# Coolant



## **AGCO OPTIMUM PREMIX 50**



AGCO OPTIMUM PREMIX is a premium quality, antiboil/anti-freeze long life coolant. AGCO premixed coolant is based on carboxylate technology and contains no silicates, borates, phosphates, amines, nitrites or nitrates. It provides protection against cavitations, erosion and wet sleeve liner pitting. The 50% mono-ethylene glycol and double inhibitor package ensure ultimate corrosion protection and extended service life. AGCO Australia approved for use in Massey Ferguson, Fendt, Challenger, Valtra and ISEKI equipment.

# **Specifications**

AS 2108.1, 2004 Type A AFNOR NFR 15-601 ASTM D3306, D4656, ASTM D4985, BS 6580 JASO J 1034 JASO M 324

## Meets The Following

GM 6277M, 1825M, 1899M MAN 324 TYPE SNF CATERPILLAR 1 EO 535 CUMMINS 92 T8-9 FORD ESE FM 97B18-C FORD ESE FM 974B4-H FORD ESE FM 99B166-C JAPENSE JIS K 2234

#### Part Numbers

5L AP5310005 20L AP5310020

# Grease



#### AGCO MP PLUS



AGCO MP PLUS is a multi-purpose extreme pressure lithium complex grease designed for wheel bearings and chassis lubrication in farming equipment. Also suitable for other applications. A blue coloured grease formulated to provide improved oxidation, increased corrosion and wear protection when compared to conventional greases. Suitable for equipment operating under severe conditions and high loads with high shock vibrations. **450G cartridge.** 

# Specifications

Part Numbers

NLGI 2

450G AP7110045 20KG AP7110020

# AGCO LITHIUM II GREASE



AGCO Lithium II Grease is a lithium-based grease formulated with the highest quality virgin base oils available, and a special additive package, which ensures anti-wear and extreme pressure properties. It is fortified with rust and corrosion inhibitors as well as oxidation inhibitors to make this a truly versatile multi-purpose lubricant. **400G cartridge.** 

Specifications

**Part Numbers** 

NLGI 2

400G 79014728W

# **Clutch & Brake Fluids**



# **AGCO PREMIUM LHM**



AGCO PREMIUM LHM is for use in brake, hydraulic, power steering and suspension systems. Always check manufacturer's booklet or seek technical advice. AGCO PREMIUM LHM brake fluid is specially formulated and designed for systems with an oil based mineral based fluid requirement. It is not compatible with traditional based brake fluids. AGCO PREMIUM LHM has base oils that provide protection against wear, corrosion and oxidation.

# **Specifications**

ISO 7308

#### **Meets The Following**

#### **Part Numbers**

1L AP6110001

## TITAN CHF 11S HYDRAULIC CLUTCH OIL



TITAN CHFS 11S is a fully synthetic high performance hydraulic oil for use in various component applications.

The exclusive additive technology combination with specifically selected base oils gives optimum performance results in hydraulic systems.

For use in Fendt machines.

# **Specifications**

FORD WSS-M2C204-A

# **Approvals**

FENDT X 902 011 622 MAN 3289 CHRSYLER MS 11655B MB APPROVAL 345.0 ZF TE-ML 02K VW TL 52 146

#### **Part Numbers**

1L FU4947001



# **Get Your Genuine AGCO Parts Lubricants**

# Contact your local AGCO Parts dealer for all your genuine AGCO Parts Lubricant needs.





