







SIMPLIFY YOUR LIFE WITH STRAIGHT-FORWARD COMFORT, CONVENIENCE AND CONTROL.

Step up to a Massey Ferguson E Series and enjoy the comfort of the spring-cushioned seat. Notice how all the controls are close at hand, easy to reach and simple to operate. Levers located to the right of the seat control the 3-point hitch. Controls for the lights and hand throttle are located on the steering column. And check out the visibility — to the ground and to the rear hitch. Now settle in and turn your "to-do" list to "done."





THE STANDARD FOLDING ROPS allow an MF E Series to fit beneath a standard 7-foot garage door.



CHOOSE THE TRANSMISSION

THAT'S RIGHT FOR YOUR WORK AND YOUR BUDGET.

MASSEY FERGUSON GIVES YOU A CHOICE OF TRANSMISSIONS ON THE MF E SERIES TRACTOR.

The rock-solid 8x8 Synchro Shuttle is a simple, mechanical gear design. With four gears and two speed ranges — you can creep along as low as .8 mph, or up to 16.6 mph — depending on tire size and type.

This transmission is ideal for jobs such as pasture mowing and field work when you want to "put it in gear and go." It also comes with a mechanical shuttle shift that simplifies loader work.

OR YOU CAN OPT UP TO THREE-RANGE HYDROSTATIC TRANSMISSION.

Simple. Smooth. Easy to use. It gives you infinite speeds within each range so you can choose the most efficient speed for any job. The hydrostatic transmission — which is controlled with the easy-to-use rocker pedal — offers the ultimate in ease and convenience. It's a great choice for loader work, mowing around objects or any other chore requiring frequent change in direction.

HYDROSTATIC TRANSMISSION FEATURES A ROCKER PEDAL CONTROL.

Press your toe down to go forward, use your heel to move in reverse. Remove your foot from the pedal and the tractor stops. So intuitive, even the most inexperienced operator can master an MF E Series in no time at all.

ALL SERVICE POINTS

Easily accessed, these service points make routine maintenance a breeze.

STRONG METAL HOOD AND FENDERS

These add to the backbone and durability of the MF E Series tractor.







PARTS & SERVICE

IT'S ALL ABOUT A LIFETIME OF SUPPORT.

Buying, owning and maintaining equipment can be complex. That's why ensuring you have support and peace of mind is always an important consideration. With Massey Ferguson, you can count on personalized, responsive support from our network of dealers. Plus, there's no cutoff time for parts and service, meaning we're available to you throughout the lifetime of your machine.

There's a pride and responsibility built into every piece of equipment we sell, and we make it our mission to keep your machine running smoothly, every single time you turn the key.

Ask your dealer about AGCO Protection, an extended warranty program that prolongs your coverage and safeguards against the cost of sudden breakdowns.



AGCO replacement parts are made to the same high standards as those used on the assembly line, so your AGCO equipment will stay running like new. Talk to your dealer or shop at parts.agcocorp.com to find the genuine AGCO parts you need.



Focus on your operation, not on scheduling maintenance. With AGCO GenuineCare plans, your service intervals are predetermined. You'll avoid downtime and be able to better plan your costs thanks to transparent pricing, bundles and discounts.





TECHNICAL SPECIFICATIONS

Tractor		1825 E	1835 E	1840 E	2850 E	2860 E
Rated Engine Power @ 2600 rpm	HP (kW)	24.0 (17.9)	34.5 (25.7)	39.4 (29.4)	48.8 (36.4)	57.3 (42.7)
PTO Power @ 540 rpm	HP (kW)	Mech: 20.4 (15.2) / HST: 19.2 (14.3)	Mech: 29.2 (21.8) / HST: 27.6 (20.6)	Mech: 33.5 (25.0) / HST: 31.5 (23.5)	Mech: 40.7 (30.4) / HST: 38.5 (28.7)	Mech: 48.0 (35.8) / HST: 45.3 (33.
Engine		Iseki, 1.49 L, 3-cyl diesel	Iseki, 1.83 l	., 3-cyl diesel	Iseki, 2.43 L	, 4-cyl diesel
Aspiration		Natural		Turboo	oocharged	
Emissions Control		None	Exhaust gas recirculation (EGR), diesel oxid		tion catalyst (DOC), diesel particulate filter (DPF)	
Mechanical Transmission		8x8 Synchro Shuttle, mechanical shuttle lever, left side of steering column				
Hydrostatic Transmission		3-range HST, mechanically controlled, foot pedal on RH side				
Hydraulic System		Open center, two gear-type pumps for steering and 3-point/remotes				
Steering Flow	gpm (Lpm)	3.6 (13.8)	3.8 (14.3)		7.0 (26.5)	
Implement Flow	gpm (Lpm)	7.3 (27.6)	7.6 (28.9)		12.6 (47.8)	
3-Point Hitch		Cat. I			Cat. I & II	
Lift Capacity – Ball Ends	lbs. (kg.)	2,205 (1,000)			2,645 (1,200)	
PTO Type		Mech: independent / HST: transmission			Independent with SoftStart electronic modulation	
Overall Length	in. (mm)	116.5 (2,960)			132.8 (3,370)	
Minimum Width	in. (mm)	52.4 (1,330)			70.1 (1,780)	
Overall Height	in. (mm)	97.6 (2,480)			103.8 (2,635)	
Ground Clearance	in. (mm)	11 (280)			15 (380)	
Base Weight	lbs. (kg.)	2,668 (1,210)	2,877	(1,305)	3,858 (1,750)	3,869 (1,755)
Fuel Tank	gal. (L)	10 (38)			14 (53)	

Loader Model		FLx2407	FLx2813	
Tractor Model		MF 1800 E Series	MF 2800 E Series	
Tool Carrier		Skid steer quick attach		
Bucket Width	in. (mm)	60 (1,500)	72 (1,850)	
Maximum Lift Height – Pivot Pin	in. (mm)	94.3 (2,394)	111 (2,818)	
Maximum Lift Height – Under Level Bucket	in. (mm)	83.8 (2128)	99.6 (2,531)	
Lift Capacity to Maximum Height – Pivot Pin	lbs. (kg.)	1,450 (659)	3,016 (1,368)	
Lift Capacity to Max. Height – 19.5 in. Forward of Pivot Pin	lbs. (kg.)	1,047 (476)	1,887 (856)	
Lift Capacity to 59 in. – Pivot Pin	lbs. (kg.)	1,437 (653)	3,406 (1,545)	
Lift Capacity to 59 in. – 19.5 in. Forward of Pivot Pin	lbs. (kg.)	1,109 (504)	2,396 (1,087)	
Breakout Force – Pivot Pin	lbs. (kg.)	2,288 (1,040)	4,176 (1,894)	
Breakout Force – 19.5 in. Forward of Pivot Pin	lbs. (kg.)	1,670 (759)	2,088 (947)	
Dump Angle		54°	38°	
Rollback Angle		26°	27°	
Digging Depth	in. (mm)	3.5 (89)	4.9 (124)	
Backhoe Model		BH3222	CB85	
Tractor Model		MF 1800 E Series	MF 2800 E Series	
Bucket Digging Force	lbs. (kg.)	3,220 (1,461)	4,072 (1,847)	
Maximum Digging Depth	in. (mm)	87 (2.22)	100 (2.50)	
Maximum Reach	in. (mm)	127 (3.22)	130 (3.30)	
Bucket Width Options	in.	9, 12, 16	10, 12, 16, 18, 24	











