



MASSEY FERGUSON

# MASSEY FERGUSON 1E SERIES

## Delivering More for Less

The Massey Ferguson® 1E Series maximizes your investment, delivering unmatched value through all-day comfort, steadfast reliability, simplicity of operation and versatility.

### COMFORT

- » Wide, tall comfortable seat for better support and less fatigue
- » Rubber comfort floor mats
- » Ground-level fueling

### VERSATILITY

- » Wide range of compatible attachments including skid steer loader bucket and backhoe
- » Compact size makes it easier to maneuver in tight spaces
- » 2000 rpm mid-PTO
- » Independent 540 rpm rear PTO
- » Cat 1 rear hitch with turnbuckle stabilizers

### EASE OF USE

- » 3-cylinder Iseki diesel engine
- » 8x8 synchro shuttle or 3-range hydrostatic transmission
- » Side-by-side hydrostatic control pedals
- » Sleek, easy-to-use instrument panel
- » Folding ROPS fits beneath 7-foot garage door



## GET MORE INFORMATION

SCAN HERE TO LEARN MORE ABOUT THE MF 1E OR TO FIND YOUR LOCAL DEALER.



BORN TO **FARM**

# TECHNICAL SPECIFICATIONS

		MF 1E.25	MF 1E.35	MF 1E.40
<b>ENGINE</b>		Iseki 1.49 L, 3-cylinder diesel		
Rated Engine Power @ 2600 rpm	HP (kW)	24.0 (17.9)	34.5 (25.7)	39.4 (29.4)
PTO Power @ 540 rpm	HP (kW)	Mech: 20.4 (15.2) HST: 19.2 (14.3)	Mech: 29.2 (21.8) HST: 27.6 (20.6)	Mech: 33.5 (25.0) HST: 31.5 (23.5)
Aspiration		Natural		Turbocharged
Emissions Control		None	Exhaust gas recirculation (EGR), diesel oxidation catalyst (DOC), diesel particulate filter (DPF)	
Fuel Tank Capacity	gal. (L)	10 (38)		
<b>TRANSMISSION</b>				
Hydrostatic		8x8 synchro shuttle with mechanical shuttle lever		
Mechanical		3-range HST with mechanically controlled foot pedal		
<b>HITCH AND HYDRAULICS</b>		Open center, two gear-type pumps for steering and 3-point remotes		
Steering Flow	GPM (LPM)	3.6 (13.8)	3.8 (14.3)	
Implement Flow	GPM (LPM)	7.3 (27.6)	7.6 (28.9)	
3-Point-Hitch Type		Cat 1		
3-Point-Hitch Lift Capacity (At Lift Points)	lbs. (kg)	2,205 (1,000)		
3-Point-Hitch Lift Capacity (24 in. Behind Lift Point)	lbs. (kg)	1,598 (725)		
<b>PTO</b>				
Type		Mech: Independent HST: Transmission		

## DIMENSIONS

		MF1E.25	MF1E.35	MF 1E.40
Overall Length	in. (mm)	116.5 (2,960)		
Minimum Width	in. (mm)	52.4 (1,330)		
Overall Height	in. (mm)	97.6 (2,480)		
Ground Clearance	in. (mm)	11 (280)		
Base Weight	lbs. (kg)	2,668 (1,210)	Mech: 2,888 (1,310), HST: 2,943 (1,335)	

## ATTACHMENTS

<b>LOADER</b>		<b>FL.2407X</b>	<b>BACKHOE</b>		<b>BH3222</b>
Tool Carrier		Skid steer quick attach	Control Type		SAE with boom float
Bucket Width	in. (mm)	60 (1,500)	Digging Depth	in. (mm)	87 (2,220)
Maximum Lift Height — Pivot Pin	in. (mm)	94.3 (2,394)	Maximum Reach	in. (mm)	127 (3,220)
Maximum Lift Height — Under Level Bucket	in. (mm)	83.8 (2,128)	Bucket Digging Force	lbs. (kg)	3,220 (1,461)
Lift Capacity to Maximum Height — Pivot Pin	lbs. (kg)	1,450 (659)	Boom Digging Force	lbs. (kg)	2,105 (955)
Lift Capacity to Maximum Height — 19.5 in. Forward	lbs. (kg)	1,047 (476)	Loading Height	in. (mm)	74 (1,881)
Lift Capacity to 59 in. — Pivot Pin	lbs. (kg)	1,437 (653)	Transport Height	in. (mm)	85 (2,161)
Lift Capacity to 59 in. — 19.5 in. Forward	lbs. (kg)	1,109 (504)	Swing Arc		180°
Breakout Force — Pivot Pin	lbs. (kg)	2,288 (1,040)	Bucket Rotation		185°
Breakout Force — 19.5 in. Forward	lbs. (kg)	1,670 (759)	Bucket Width Options	in.	9, 12, 16
Dump Angle		54°			
Rollback Angle		26°			
Digging Depth	in. (mm)	3.5 (89)			

\*Specifications are manufacturer's estimates at time of publication and are subject to change without prior notification.