



MASSEY FERGUSON

MASSEY FERGUSON 2E SERIES

A Perfect Balance of Comfort, Efficiency and Versatility

The Massey Ferguson® 2E Series packs the power and versatility of a larger tractor into an economical, easy-to-use package. Designed for hobby farmers, property owners and businesses, it handles any task easily all at a low cost of ownership.

COMFORT

- » Wide, tall comfortable seat for better support and less fatigue
- » Rubber comfort floor mats
- » Optional R14 tires
- » Ground-level fueling

VERSATILITY

- » Wide range of compatible attachments, including skid steer loader bucket and backhoe
- » Bigfoot (oversized) stabilizer pads
- » Street (rubber) stabilizer pads
- » Mechanical thumb
- » Cat 1 rear hitch with turnbuckle stabilizers or optional Cat 1 quick hitch

EASE OF USE

- » 2.43L, 4-cylinder Iseki diesel engine
- » 8x8 synchro shuttle or 3-range hydrostatic transmission
- » Side-by-side hydrostatic control pedal
- » One-piece tilt-up hood
- » Sleek, easy-to-use instrument panel
- » Key-operated electronic fuel shutoff and glow plug



GET MORE INFORMATION

SCAN HERE TO LEARN MORE ABOUT THE MF 2E OR TO FIND YOUR LOCAL DEALER.



BORN TO **FARM**

TECHNICAL SPECIFICATIONS

		MF 2E.50	MF 2E.60
ENGINE		Iseki 2.43L 4-cylinder diesel	
Rated Engine Power @ 2600 rpm	HP (kW)	48.8 (36.4)	57.3 (42.7)
PTO Power @ 540 rpm	HP (kW)	Mech: 40.7 (30.4) HST: 38.5 (28.7)	Mech: 48.0 (35.8) HST: 45.3 (33.8)
Aspiration		Turbocharged	
Emissions Control		Exhaust gas recirculation (EGR), diesel oxidation catalyst (DOC), diesel particulate filter (DPF)	
Fuel Tank Capacity	gal. (L)	14 (53)	
TRANSMISSION			
Hydrostatic		8x8 synchro shuttle with mechanical shuttle lever	
Mechanical		3-range HST with mechanically controlled foot pedal	
HITCH AND HYDRAULICS		Open center, two gear-type pumps for steering and 3-point remotes	
Steering Flow	GPM (LPM)	7.0 (26.5)	
Implement Flow	GPM (LPM)	12.6 (47.8)	
3-Point-Hitch Type		Cat 1 & 2	
3-Point-Hitch Lift Capacity (At Lift Points)	lbs. (kg)	2,645 (1,200)	
3-Point-Hitch Lift Capacity (24 in. Behind Lift Point)	lbs. (kg)	2,425 (1,100)	
PTO			
Type		Independent w/SoftStart electronic modulation	

DIMENSIONS

		MF 2E.50	MF 2E.60
Overall Length	in. (mm)	132.8 (3,370)	
Minimum Width	in. (mm)	70.1 (1,780)	
Overall Height	in. (mm)	103.8 (2,635)	
Ground Clearance	in. (mm)	15 (380)	
Base Weight	lbs. (kg)	3,858 (1,750)	3,869 (1,755)

ATTACHMENTS

LOADER		FL2813X	BACKHOE		CB85
Tool Carrier		Skid steer quick attach	Control Type		SAE with Boom Float
Bucket Width	in. (mm)	72 (1,850)	Digging Depth	in. (mm)	100 (2,500)
Maximum Lift Height — Pivot Pin	in. (mm)	111 (2,818)	Maximum Reach	in. (mm)	130 (3,300)
Maximum Lift Height — Under Level Bucket	in. (mm)	99.6 (2,531)	Bucket Digging Force	lbs. (kg)	4,072 (1,847)
Lift Capacity to Maximum Height — Pivot Pin	lbs. (kg)	3,016 (1,368)	Boom Digging Force	lbs. (kg)	1,189 (2,621)
Lift Capacity to Maximum Height — 19.5 in. Forward	lbs. (kg)	1,887 (856)	Loading Height	in. (mm)	76 (1,900)
Lift Capacity to 59 in. — Pivot Pin	lbs. (kg)	3,406 (1,545)	Transport Height	in. (mm)	87 (2,200)
Lift Capacity to 59 in. — 19.5 in. Forward	lbs. (kg)	2,396 (1,087)	Swing Arc		175°
Breakout Force — Pivot Pin	lbs. (kg)	4,176 (1,894)	Bucket Rotation		180°
Breakout Force — 19.5 in. Forward	lbs. (kg)	2,088 (947)	Bucket Width Options	in.	10, 12, 16, 18, 24
Dump Angle		38°			
Rollback Angle		27°			
Digging Depth	in. (mm)	4.9 (124)			

*Specifications are manufacturer's estimates at time of publication and are subject to change without prior notification.