



MASSEY FERGUSON

# MASSEY FERGUSON 1M.25

## The All-in-One Property Management Tool

The Massey Ferguson® 1M.25 delivers unbeatable value, blending all-day comfort, reliability and the legendary ease of use that defines Massey Ferguson equipment.

### COMFORT

- » Wide, tall comfortable seat for better support and less fatigue
- » Platform option with folding ROPS that fits beneath 7-foot garage door
- » Spacious operator station and cab puts necessary controls right at your fingertips

### VERSATILITY

- » Wide range of compatible attachments including snow removal equipment, mid-mount mower, skid steer loader bucket and backhoe
- » Cab or platform configurations available to fit your needs
- » Independent, 540 rpm rear PTO
- » 2000 rpm mid-PTO (optional)

### EASE OF USE

- » 1.49L, 3-cylinder Iseki diesel engine
- » 3-range hydrostatic transmission
- » Side-by-side hydrostatic control pedals
- » Sleek, easy-to-use instrument panel
- » Available LED work lights



## GET MORE INFORMATION

SCAN HERE TO LEARN MORE ABOUT THE MF 1M.25 OR TO FIND YOUR LOCAL DEALER.



BORN TO **FARM**

# TECHNICAL SPECIFICATIONS

MF 1M.25		
<b>ENGINE</b>		
		Iseki 3-cylinder diesel
Rated Engine Power @ 2600 rpm	HP (kW)	24.8 (18.5)
PTO Power @ 540 rpm	HP (kW)	ROPS: 18.2 (13.6) CAB: 16.9 (12.6)
Fuel Tank Capacity	gal. (L)	7.4 (28)
<b>TRANSMISSION</b>		
Mechanical		3-range HST with mechanically controlled foot pedal
<b>HITCH AND HYDRAULICS</b>		
		Open center
Steering Flow	GPM (LPM)	3.2 (12.1)
Implement Flow	GPM (LPM)	5.5 (20.9)
3-Point-Hitch Type		Cat 1
3-Point-Hitch Lift Capacity (At Lift Points)	lbs. (kg)	1,433 (650)
3-Point-Hitch Lift Capacity (24 in. Behind Lift Point)	lbs. (kg)	1,091 (495)
<b>PTO</b>		
Type		Independent
<b>OPERATOR STATION</b>		
		Platform or cab
ROPS		Foldable

## DIMENSIONS

MF1M.25		
Overall Length	in. (mm)	116 (2,945)
Minimum Width	in. (mm)	45.7-52 (1160-1320)
Overall Height	in. (mm)	ROPS: 95.3-97.5 (2420-2475) Cab: 80-82.1 (2030-2085)
Ground Clearance	in. (mm)	9.9-11 (250-305)
Base Weight	lbs. (kg)	ROPS: 2044 (927) Cab: 2,169 (84)

## ATTACHMENTS

LOADER		FL.2106	MID-MOUNT MOWER	1506
Tool Carrier		Skid Steer	Discharge	Right side
Bucket Width	in.	54	Cutting Width	in. (mm)
Maximum Lift Height — Pivot Pin	in. (mm)	83 (2,108)	Cutting Height	in. (mm)
Maximum Dump Angle		42°	Number of Blades	3
Maximum Rollback Angle		31°	Max Blade Tip Velocity	ft./sec. (m/sec.)
Digging Depth	in. (mm)	1.6 (40)		320.2 (97.6)
Lift Capacity to Maximum Height — Pivot Pins	lbs. (kg)	1,222 (554)		
Lift Capacity to Maximum Height — 19.5 in. Forward	lbs. (kg)	852 (386)		
Breakout Force — Pivot Pins	lbs. (kg)	1,822 (826)		
Breakout Force — 19.5 in. Forward	lbs. (kg)	1,282 (582)		
Lift Cylinder Diameter	in. (mm)	2 x 1.77 (45)		
Bucket Cylinder Diameter	in. (mm)	2 x 1.77 (45)		

\*Specifications are manufacturer's estimates at time of publication and are subject to change without prior notification.