



MASSEY FERGUSON

MASSEY FERGUSON 2M SERIES

Elevate Your Operation

The Massey Ferguson® 2M Series redefines premium compact tractors, delivering exceptional value and unmatched productivity. Built rugged yet remarkably versatile, these machines offer extensive customization options to perfectly match your unique needs.

COMFORT

- » Wide, tall comfortable seat for better support and less fatigue
- » LED lighting package
- » Ground-level fueling
- » Rear defroster
- » Radio hookup

VERSATILITY

- » Wide range of compatible attachments, including snow removal equipment, skid steer loader bucket and backhoe.
- » Classic or Deluxe cab options
- » Rear remote valve and lever

EASE OF USE

- » 2.43L, 4-cylinder Iseki diesel engine
- » 12x12 power shuttle or 3-range hydrostatic transmission
- » 3-Range hydrostatic transmission (*all models*), 2 stages (Hi & Lo) Servo-HST (*2M.65 ONLY*)
- » 1.1L, 3-cylinder liquid-cooled Iseki diesel engine
- » Folding ROPS fits beneath 7-foot garage door



GET MORE INFORMATION

SCAN HERE TO LEARN MORE ABOUT THE MF 2M OR TO FIND YOUR LOCAL DEALER.



BORN TO **FARM**

TECHNICAL SPECIFICATIONS

		MF 2M.50	MF 2M.60	MF 2M.65
ENGINE		Iseki 2.43L, 4-cylinder diesel		
Rated Engine Power @ 2,600 rpm	HP (kW)	48.8 (36.4)	60.3 (45.0)	65.7 (49)
PTO Power @ 540 rpm	HP (kW)	Mech: 38.1 (28.4) HST: 36.2 (27.0)	Mech: 47.0 (35.0) HST: 44.6 (33.3)	HST ONLY: 50 (37.2)
Aspiration		Aspiration Turbocharged		
Emissions Control		Exhaust gas recirculation (EGR), diesel oxidation catalyst (DOC), diesel particulate filter (DPF)		
Fuel Tank Capacity	gal. (L)	14.0 (53)		
TRANSMISSION				
Hydrostatic		3-range hydrostatic transmission, Servo-HST, electronically controlled		3-range hydrostatic transmission, 2 stages (Hi & Lo) Servo-HST, electronically controlled
Mechanical		12x12 power shuttle with electronic shuttle lever		N/A
HITCH AND HYDRAULICS		Open center, two gear-type pumps for steering and 3-point remotes		
Steering Flow	GPM (LPM)	7.1 (26.7)		
Implement Flow	GPM (LPM)	Mech: 12.7 (48.0), HST: 12.6 (47.8)		HST ONLY: 12.6 (47.8)
3-Point-Hitch Type		Type Cat I & II		
3-Point Hitch Lift Capacity (At Lift Points) Mechanical	lbs. (kg)	3,483 (1,580)	3,747 (1,700)	N/A
3-Point Hitch Lift Capacity (At Lift Points) HST		3,483 (1,580)		
3-Point Hitch Lift Capacity (24 in. Behind Lift Point) Mechanical	lbs. (kg)	3,086 (1,400)	3,307 (1,500)	
3-Point Hitch Lift Capacity (24 in. Behind Lift Point) HST		3,086 (1,400)		HST ONLY: 3,483 (1,580)
PTO				
Type		Independent with SoftStart electronic modulation		

DIMENSIONS

		MF 2M.50	MF 2M.60	MF 2M.65
Overall Length	in. (mm)	132.3 (3,360)	Mech: 136.2 (3,460), HST: 132.3 (3,360)	132.3 (3,360)
Minimum Width	in. (mm)	70.1 (1,780)	71.3 (1,810)	70.1 (1,780) : HST ONLY
Overall Height	in. (mm)	ROPS: 102.4 (2,600), Cab: 92.9 (2,360)	ROPS: 103.1 (2,620), Cab: 93.3 (2,370)	Cab ONLY: 92.9 (2,360)
Ground Clearance	in. (mm)	14.0 (355)	Mech: 11.6 (295), HST: 14.0 (355)	14.0 (355)
Base Weight	lbs. (kg)	ROPS: 4,035 (1,830), Cab: 4,420 (2,005)	ROPS: 4,288 (1,945), Cab: 4,674 (2,120)	Cab ONLY: 4,608 (2,090)

ATTACHMENTS

		LOADER	FL2814	BACKHOE*	CB85	
Tool Carrier			Skid steer	Control Type	SAE with boom float	
Bucket Width	in. (mm)	in. (mm)	72 (1,850)	Digging Depth	in. (mm)	100 (2,500)
Maximum Lift Height — Pivot Pin	in. (mm)	in. (mm)	111 (2,830)	Maximum Reach	in. (mm)	130 (3,300)
Maximum Lift Height — Under Level Bucket	in. (mm)	in. (mm)	104 (2,630)	Bucket Digging Force	lbs. (kg)	4,072 (1,847)
Lift Capacity to Maximum Height — Pivot Pin	lbs. (kg)	lbs. (kg)	2,570 (1,170)	Boom Digging Force	lbs. (kg)	1,189 (2,621)
Lift Capacity to Maximum Height — 19.5 in. Forward	lbs. (kg)	lbs. (kg)	1,880 (850)	Loading Height	in. (mm)	76 (1,900)
Lift Capacity to 59 in. — Pivot Pin	lbs. (kg)	lbs. (kg)	3,010 (1,370)	Transport Height	in. (mm)	87 (2,200)
Lift Capacity to 59 in. — 19.5 in. Forward	lbs. (kg)	lbs. (kg)	2,420 (1,100)	Swing Arc		175°
Breakout Force — Pivot Pin	lbs. (kg)	lbs. (kg)	3,910 (1,770)	Bucket Rotation		180°
Breakout Force — 19.5 in. Forward	lbs. (kg)	lbs. (kg)	2,960 (1,340)	Bucket Width Options	in.	10, 12, 16, 18, 24
Dump Angle			48°			
Rollback Angle			46°			
Digging Depth	in. (mm)		2.8 (70)			

*currently fits 2M.50 & 2M.60 models only

*Specifications are manufacturer's estimates at time of publication and are subject to change without prior notification.

