



MASSEY FERGUSON

MASSEY FERGUSON 1M SERIES

Achieve More With Premium Features and Enhanced Capability

Why settle for less when you can have it all with the Massey Ferguson® 1M Series? Whether you're a first-time owner or a seasoned pro, work smarter not harder with available cab options, rugged durability, premium features and intuitive controls.

COMFORT

- » Wide, tall comfortable seat for better support and less fatigue
- » Ground-level fueling
- » Cruise control
- » Radio hookup
- » Rear defroster
- » LED lighting package (optional)
- » R14 tires (optional)

VERSATILITY

- » Wide range of compatible attachments including skid steer loader bucket and backhoe
- » Classic or Deluxe cab options
- » Cat 1 3-point-hitch and optional quick hitch
- » Factory-installed rear remote valves

EASE OF USE

- » 1.83L, 3-cylinder Iseki diesel engine
- » 12x12 power shuttle or 3-range hydrostatic transmission
- » Backup alarm wiring



GET MORE INFORMATION

SCAN HERE TO LEARN MORE ABOUT THE MF 1M OR TO FIND YOUR LOCAL DEALER.



BORN TO **FARM**

TECHNICAL SPECIFICATIONS

		MF 1M.35	MF 1M.40
ENGINE		Iseki 1.83L, 3-cylinder diesel	
Rated Engine Power @ 2600 rpm	HP (kW)	36.2 (27.0)	39.4 (29.4)
PTO Power @ 540 rpm	HP (kW)	Mech: 27.5 (20.5) HST: 25.7 (19.2)	Mech: 30.0 (22.4) HST: 27.9 (20.8)
Aspiration		Turbocharged	
Emissions Control		Exhaust gas recirculation (EGR), diesel oxidation catalyst (DOC), diesel particulate filter (DPF)	
Fuel Tank Capacity	gal. (L)	10.6 (40)	
TRANSMISSION			
Hydrostatic		3-range hydrostatic transmission, Servo-HST, electronically controlled	
Mechanical		12x12 power shuttle with electronic shuttle lever	
HITCH AND HYDRAULICS		Open center, two gear-type pumps for steering and 3-point remotes	
Steering Flow	GPM (LPM)	7.0 (26.5)	
Implement Flow	GPM (LPM)	12.6 (47.8)	
3-Point-Hitch Type		Cat 1	
3-Point-Hitch Lift Capacity (At Lift Points)	lbs. (kg)	2,800 (1,270)	
3-Point-Hitch Lift Capacity (24 in. Behind Lift Point)	lbs. (kg)	2,535 (1,150)	
PTO			
Type		Independent with SoftStart electronic modulation	

DIMENSIONS

		MF 1M.35	MF 1M.40
Overall Length	in. (mm)	122.0 (3,100)	
Minimum Width	in. (mm)	67.5 (1,715)	
Overall Height	in. (mm)	ROPS: 99.2 (2,520), Cab: 91.3 (2,320)	
Ground Clearance	in. (mm)	14.4 (365)	
Base Weight	lbs. (kg)	ROPS: 3,472 (1,575), Cab: 3,858 (1,750)	

ATTACHMENTS

LOADER			FL2611	BACKHOE		CB75
Tool Carrier			Skid steer	Control Type		SAE with boom float
Bucket Width	in. (mm)	in. (mm)	66 (1,700)	Digging Depth	in. (mm)	92 (2,300)
Maximum Lift Height — Pivot Pin			100 (2,550)	Maximum Reach	in. (mm)	120 (3,000)
Maximum Lift Height — Under Level Bucket			93 (2,350)	Bucket Digging Force	lbs. (kg)	3,082 (1,398)
Lift Capacity to Maximum Height — Pivot Pin			1,870 (850)	Boom Digging Force	lbs. (kg)	2,015 (914)
Lift Capacity to Maximum Height — 19.5 in. Forward			1,380 (630)	Loading Height	in. (mm)	70 (1,800)
Lift Capacity to 59 in. — Pivot Pin			2,220 (1,010)	Transport Height	in. (mm)	76 (1,900)
Lift Capacity to 59 in. — 19.5 in. Forward			1,750 (790)	Swing Arc		175°
Breakout Force — Pivot Pin			2,950 (1,340)	Bucket Rotation		174°
Breakout Force — 19.5 in. Forward			2,170 (980)	Bucket Width Options	in.	10, 12, 16, 18, 24
Dump Angle			55°			
Rollback Angle			42°			
Digging Depth			in. (mm)	4.3 (110)		

*Specifications are manufacturer's estimates at time of publication and are subject to change without prior notification.